


FEATURES

- PROPRIETARY *SOFT GLASS*[®] JUNCTION PASSIVATION FOR SUPERIOR RELIABILITY AND PERFORMANCE
- VOID FREE VACUUM DIE SOLDERING FOR MAXIMUM MECHANICAL STRENGTH AND HEAT DISSIPATION (Solder Voids: Typical $\leq 2\%$, Max. $\leq 10\%$ of Die Area)
- LOW SWITCHING NOISE
- LOW THERMAL RESISTANCE
- HIGH SWITCHING CAPABILITY
- LOW FORWARD VOLTAGE DROP

Mechanical Data

- Case: JEDEC DO-27 molded epoxy (U/L Flammability Rating 94V-0)
- Terminals: Plated axial leads
- Solderability: Per MIL-STD 202 Method 208 guaranteed
- Polarity: Color band denotes cathode
- Mounting Position: Any
- Weight: 0.04 Ounces (1.12 Grams)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive loads, derate current by 20%.

PARAMETER (TEST CONDITIONS)	SYMBOL	RATINGS									UNITS
		UFR 300	UFR 301	UFR 302	UFR 303	UFR 304	UFR 305	UFR 306	UFR 308	UFR 310	
Maximum DC Blocking Voltage	V _{RM}	50	100	200	300	400	500	600	800	1000	VOLTS
Maximum RMS Voltage	V _{RMS}	35	70	140	210	280	350	420	560	700	
Maximum Peak Recurrent Reverse Voltage	V _{RRM}	50	100	200	300	400	500	600	800	1000	
Average Forward Rectified Current @ T _A = 55 °C	I _O	3									AMPS
Peak Forward Surge Current (8.3mS single half sine wave superimposed on rated load)	I _{FSM}	160									
Maximum Forward Voltage at 3 Amps DC	V _{FM}	1.25			1.7						VOLTS
Maximum Average DC Reverse Current @ T _C = 25° C At Rated DC Blocking Voltage @ T _C = 125° C	I _{RM}				5 50						μA
Typical Thermal Resistance, Junction to Lead	R _{θJA}				20						°C/W
Typical Junction Capacitance (Note 1)	C _J				45						pF
Maximum Reverse Recovery Time (I _F =0.5A, I _R =1A, I _{RR} =0.25A)	T _{RR}	50			75						nSec
Junction Operating and Storage Temperature Range	T _J , T _{STG}	-65 to +150									°C

NOTES: (1) Measured at 1 MHz and an applied reverse voltage of 4 volts.

RATINGS AND CHARACTERISTIC CURVES

UFR300 THRU UFR310




FIGURE 1. FORWARD CURRENT DERATING CURVE




FIGURE 2. MAXIMUM NON-REPETITIVE SURGE CURRENT




FIGURE 3. TYPICAL FORWARD CHARACTERISTICS




FIGURE 4. TYPICAL REVERSE CHARACTERISTICS




FIGURE 5. TYPICAL JUNCTION CAPACITANCE